



FUME EXTRACTORS

Applications

Medium to Heavy Fabrications
 Repair and Service Stations
 Chemical Laboratory
 Mixing Stations etc.,

Processes

MIG Welding
 TIG Welding
 Arc Welding
 Laser Cutting
 Drilling Machine

Power

1,2,3 & 5HP Models

Sound Level

70-80 dB

Filtration Used

3-Stage Filtration

Input Power

3 Phase, 415V, 50Hz


Material

Mild Steel/Stainless Steel

Specification Table

Model	Power (hp)	Airflow (m ³ /Hr)	Static Pressure (mm of H ₂ O)	Arm Configurations		
				Diameter (mm)	Length (m)	Qty
FMC 1.0	1	1400	100	ø100	2	1
FMC 2.0	2	1850	100	ø100	2.5	1
FMC 3.0	3	1950	150	ø100	2.5	2
				ø160	2.5	1





Contact US
Dynavac India Private Limited
 Coimbatore - 641 007, TN, India
 ✉ sales@dynavac.org
 ☎ 0422 4525555 / 96776 00302
 🌐 www.dynavac.in

Our Products

- ◆ Industrial Vacuum Cleaners
- ◆ Dust Collectors
- ◆ Centrifugal Blowers
- ◆ Downdraft Tables
- ◆ Fume Extractors
- ◆ Vacuum Loaders
- ◆ Wet Scrubbers
- ◆ Ring Blowers